

SYDNEY GLASS LIFTERS

GLASS LIFTING EQUIPMENT HIRE

P: 0411 429 813 E: HIRE@GLASSLIFTERS.COM.AU W: WWW.GLASSLIFTERS.COM.AU

SGL 3000

WLL: 3000kg



Description

- Used for handling flat and curved glass with a radius of > 3m
- 2 independent vacuum circuits, each vacuum circuit with 2-fold safety intergrated vacuum reservior
- Suction frame can be hydrualically tilted by 90 degrees, rotated electronically driven by 360 degrees
- Blow off function for releasing glass

Suction Frame	Frame with 32 suction pads, Working Load Limit up to 1,560 kg 2 extensions and 50 suction pads, Working Load Limit up to 2,440 kg 4 extensions and 62 suction pads, Working Load Limit up to 3,000 kg
Weight	950kg
Vacuum Generation	Electrical vacuum pump
Operation	Cabel remote controll, radio remote controll
Vacuum system	Dual Circuit vacuum system for construction site use
Nominal pressure pneumatic system	-0.65 bar to -0.73 bar
Power Supply	24 V DC battery system
Movement	Hydraulic 360° rotation on suction frame, 360° rotation on hook. Hydraulic 90° Tilting

SYDNEY GLASS LIFTERS

15 Short Street, Gladesville, NSW 2111 | Mobile: 0411.429.813 | Fax: 02.9618.2145 | www.glasslifters.com.au | hire@glasslifters.com.au

SYDNEY GLASS LIFTERS

GLASS LIFTING EQUIPMENT HIRE

P: 0411 429 813 E: HIRE@GLASSLIFTERS.COM.AU W: WWW.GLASSLIFTERS.COM.AU



SYDNEY GLASS LIFTERS

15 Short Street, Gladesville, NSW 2111 | Mobile: 0411.429.813 | Fax: 02.9618.2145 | www.glasslifters.com.au | hire@glasslifters.com.au