

SYDNEY GLASS LIFTERS

GLASS LIFTING EQUIPMENT HIRE

P: 0411 429 813 E: HIRE@GLASSLIFTERS.COM.AU W: WWW.GLASSLIFTERS.COM.AU

SGL-900 SWL 900KG



SGL 900

- SWL is 12 pads (900kg) 10 pads (750kg) and 6 pads (450kg)
- Option of turning off individual vacuum pads
- Narrow design 190mm from face of pads to back of lift bar
- Narrow design is perfect for glazing between scaffold and the building
- Lift bar is 860mm from pivot point
- Dual Vacuum system provides safer lifting
- Battery operated
- Complies with As 4991-2004 requirements

Min Glass Size	800mm x 1450mm (at 450kg capacity) / 2200mm x 1360mm (at 750kg or 900kg capacity)
Lift Capacity	450kg / 750kg / 900kg
Total Rig Weight	120kg
Rig Size	1300mmL x 780mmW SWL450kg/ 1300mmL x 2180mmW SWL900kg(with extension arms)
Tilt	Manual - 90 degrees with hydraulic tilt assist to hold load at any angle
Rotate	Manual - 360 degrees unlimited, locks in every 90 degrees

SYDNEY GLASS LIFTERS

15 Short Street, Gladesville, NSW 2111 | Mobile: 0411.429.813 | Fax: 02.9618.2145 | www.glasslifters.com.au | hire@glasslifters.com.au